



IPC 2U-2129L

The **IPC 2U-2129L** is the perfect rack for a low-priced server system. The excellent quality of the materials combined with superb workmanship establishes the basis for a very variable case.

For example the **IPC 2U-2129L** provides the possibility to mount a 2U server power supply in the rear of the cage or as an economic alternative a normal ATX power supply in the front. So if you want to operate this case with a server power supply you just have to exchange the rear HDD-cage with the ATX power supply bracket and remove the rear fan bracket.

Additionally the **IPC 2U-2129L** is equipped with a standard 80mm fan, block connectors for the front fans, perforated slot brackets and dust filters in the front. This guarantees an optimal cooling of the assembled components.

Specifications

Motherboard	ATX, µATX, eATX, SSI EEB
Drive Bays	5.25" external: 3 3.5" external: 0 3.5" internal: 6
Front Connectors	USB 2.0: 2
Cooling System	Inter: 4x 80mm Rear: 1x 80mm (included, Molex connector)
Controls	Power-Button Reset-Button
LED	Power HDD Activity 2x Network Activity
Power Supply	2U Server PSU ATX PSU
Material	1.0-1.2mm Steel
Packing Units	Shipping Unit: 1 Piece Pallet: 18 Pieces
Guarantee and Warranty	Case 24 Months Warranty
Article Number	88887028
EAN-Code	4260133123403
Scope of Delivery	Screw Set Mounting frame for 2HU PSU
Features	Dust filter Possibility to mount a 2U server PSU in the rear or a ATX PSU in the front Standard 1x 80mm rear fan Removable and optional positionable HDD-cages Slot brackets screwed and perforated (rear) Degradable rack brackets

Dimensions and Weight

	Cage	Case	Package
Height	95mm	95mm	175mm
Width	430mm	485mm	560mm
Depth	620mm	670mm	755mm

Weight (net): 7.96Kg
Weight (gross): 9.65Kg

Power supply

Connector	Quantity	Max. Length
Mainboard 20+4Pin	-	-
P4 12V 4Pin	-	-
P4/EPS 4+4Pin	-	-
P8 12V 8Pin	-	-
PCI-Express 6+2Pin	-	-
PCI-Express 6Pin	-	-
IDE 4Pin	-	-
S-ATA	-	-
Floppy	-	-
RPM sensor cable	-	-
Fan control	-	-
Fan 120mm	-	-

Certification:

